Pen&inc. DESIGN AND PREPRESS
9860 S. Franklin Dr, Franklin, WI 53132
P 414.421.8262 F 414.421.1594
E contact_us@pen-and-inc.com
visit us online: pen-and-inc.com

220801002
JOB NUMBER DATE: 08/02/22

R1: 08/08/22	R2: 08/22/22	R3: 09/06/22	R4: 09/08/22
R5:	R6:	R7:	R8:

CHECK & SIGN: ___ ITEM APPROVED ___ APPROVED WITH NOTED CHANGES ___ NOT APPROVED

SIGNATURE: _____ DATE: _____

PLEASE REVIEW THIS PROOF for copy, content, dimensional layout, color break, bar code, metallic areas, etc. Spot colors are simulated for this proof. Your approval confirms accuracy of the graphics and all information. Pen and Inc. will not be responsible for any errors or omissions after proof is approved.

LIMITATION OF LIABILITY: This proof must be thoroughly inspected upon receipt of the same. It is the responsibility of the recipient to examine all electronic files, proofs, films and plates, prior to printing. If errors are found, please contact our Customer Service Department. The liability of Pen and Inc. shall be limited to correcting or replacing its own product. Pen and Inc. will not be liable for any other loss or damage including, but not limited to, the cost of electronic files, proofs, films, printing plates or cylinders, printed material, overtime, press delays or downtime, and/or missing insertion dates/deadlines.

LINE BLACK	SCREEN BLACK	LINE PMS 2035	LINE PMS 7509	LINE PMS 116	SCREEN CYAN
Kodak NXH 8.7% INK COV.	150 LPI Kodak NXH 13.7% INK COV.	Kodak NXH 75.5% INK COV.	Kodak NXH 9.4% INK COV.	Kodak NXH 0.1% INK COV.	150 LPI Kodak NXH 1.3% INK COV.

SCREEN MAGENTA	SCREEN YELLOW	LINE HD WHITE
150 LPI Kodak NXH 4.1% INK COV.	150 LPI Kodak NXH 2.8% INK COV.	Kodak NXH 96.1% INK COV.

PROOF ORIENTATION DOES NOT REPRESENT FINAL UNWIND

REPRESENTS FOIL

REPRESENTS WHITE

REPRESENTS DIELINE DOES NOT PRINT

incspot

INFLX_Alpha_NXf38A01L150kdkR

PROFILE DATE: ***11/8/17*** TARGET VALUES: ***Custom***

	ΔE	L	*a	*b	*C	h°	TVI Min	TVI 25	TVI 50	TVI 75	Anilox/BCM	Anilox ID	Viscosity	Density
Y	4	91.9	-7.8	99.5	99.8	94.4	17	50	73	89	1200 / 1.7			1.04
M	4	47.7	74.2	7.6	74.8	6	13	43	69	87	1200 / 1.7			1.43
C	4	52.7	-33.7	-53.6	63.4	238	17	46	71	89	1200 / 1.7			1.52
K	4	15.6	1.5	2.4	2.8	58	15	51	75	87	1200 / 1.7			1.66
					TVI Tolerances		+/-	+/- 5	+/- 5	+/- 5				

Ink System	Mounting Tape	Substrate	Orientation	Plate Material	LPI
	3M 1320		Reverse	Kodak NXH	150

THE LISTED PRESS PROFILE INFORMATION IS BASED ON THE RESULTS OF PRESS CHARACTERIZATION TESTING THAT WAS DONE TO PRODUCE THE PROOFING PROFILE. THE ABOVE INFORMATION IS REPRESENTATIVE OF THE PRESS CONDITIONS DURING THE PRESS CHARACTERIZATION AND SHOULD BE USED AS A TARGET FOR STARTUP OF THE PRESS APPROVAL PROCESS.

NOTE – CONTRACT INKJET PROOFS ARE ACCURATE FOR COLOR READINGS ONLY (LAB/LCH). USE THE TABLE ABOVE FOR LAB AND TONAL VALUE INCREASE (TVI) TARGETS. ***VISCOSITY AND DENSITY ARE ADVISORY TARGETS AND CAN CHANGE DEPENDING ON CONDITIONS.***

COLOR MATCHING INFO FOR PRINTERS

PMS Colors: *Match to Digital Pantone Library*

Image/Process Elements: *Match to GMG Open Color Profiled Proof*

Profiled Proof includes Compensation for Substrate Color

Spectro Standards
Delta E Formula: *Delta E2000*
Tolerance: *Delta E <2.0*
Illuminant: *D50*
Filter: *M1*
Observer Angle: *2°*
Recommended Device: *X-Rite Exact*
XRGA: *Yes*
Rendering Intent: *Absolute*

P 100C 25M 75Y 50K CY 50/40/40 75M 25Y 100K 25C MY 75/64/64 50C 25/19/19 100M 50Y 25K CM P 75C 50M 100Y 75K P 1C 1M 1Y 1K